

MB117 Paving Breaker

The MB117A pneumatic pavement breaker from Mindrill are useful for heavy breaker applications. They have a high blow impact, specially when their low weight and low air consumption are taken into consideration. The drill also has an integral oiler system to provide lubrication and is available in two shank sizes.

Key Features:

- Traditional design accounts for widely available spare parts
- Powerful blow impact with respect to weight
- Lightweight and low air consumption
- Integral oiler system for continuous lubrication
- Low maintenance cost

Options:

- Kick latch retainer model - MB117L
- Chuck sizes - 28 mm X 160 mm (1¹/₈"X6¹/₄") & 32 mm X 160 mm (1¹/₄"X6¹/₄")



SPECIFICATIONS

	MB117		MB117L	
	Metric	Imperial	Metric	Imperial
Weight	35 kg	77 lb	39 kg	85 lb
Length	740 mm	29"	740 mm	29"
Piston Diameter	57 mm	2 ¹ / ₄ "	57 mm	2 ¹ / ₄ "
Piston Stroke	212 mm	8 ¹ / ₄ "	212 mm	8 ¹ / ₄ "
Air consumption	35 l/s @ 6 bar	75 cfm @ 90 psi	35 l/s @ 6 bar	75 cfm @ 90 psi
Air Inlet	3/4"NPTF		3/4"NPTF	
Impact Rate	1080 BPM		1080 BPM	
Retainer type	Spring		Latch	

Ordering Part Numbers:

	MB117	MB117L
28 mm X 160 mm (1 ¹ / ₈ "X6 ¹ / ₄ ")	5112 101 000 28	5112 108 000 28
32 mm X 160 mm (1 ¹ / ₄ "X6 ¹ / ₄ ")	5112 101 000 32	5112 108 000 32

MANUFACTURING SYSTEMS CERTIFIED BY TUV NORD ISO 9001:2008

MINDRILL SYSTEMS & SOLUTIONS PVT. LTD. is constantly striving to improve it's products and therefore reserves the right to modify materials, specifications and designs without prior notice. Technical data described here corresponds with the available information at the time of issue of design.

BUILT IN INDIA

Mindrill Systems & Solutions Pvt. Ltd.
NH6, Domjur Mahiary Road, Vill-Biparnapara, P.O-Begri, P.S-Domjur,
Near Saraswati Bridge-Domjur, Howrah-711411, West Bengal, India.

Export Sales: +91 98303 92522 | Domestic Sales: +91 98303 06673

Website: www.mindrill.com
E-mail: marketing@mindrill.com