

DTH Hammer MD120

Key Features:

- Optimal for hard and abrasive rocks
- Heavy-duty or reversible casting for long life
- Advanced shank design for maximum energy efficiency
- High penetration rate
- Low running and maintenance costs
- Control tube sub assembly is used for guiding piston which minimizes the service requirements
- Hammer is inbuilt with buffer ring which will sustain the compressive load generated from drill string

Specifications:

| Specification | Metric |
|-----------------|-------------------------|
| Length W/o bit | 980.0 mm |
| Outside dia | 107.0 mm |
| Weight | 47.0 kg |
| Cylinder bore | 88.0 mm |
| Piston stroke | 80.0 mm |
| Piston weight | 10.5 kg |
| Hole sizes | 120-140 mm |
| Wrench size A/F | A/F 74.5 mm / W-40.0 mm |
| Suitable shank | 4-3/4in K4 Button Bit |

Ordering Part No. :

| | |
|----------|--------------|
| 4 3/4 in | 5142 114 000 |
|----------|--------------|



Issue no 2, Issue date 09/07/2022



Reliability Unparalleled. Power Unmatched.

Export Sales: +91 98303 92522 | Domestic Sales: +91 98305 52526 | Website: www.mindrill.com
Email: marketing@mindrill.com